



EASYKIT

FOR A COMPLETE CHECK-UP OF YOUR BELT DRIVE



A sudden fever?

Hutchinson thermocouple



- Measuring range : -200°C to +1.500°C
- Reading : 0.1°C from -200°C to +999°C
1.0°C from 1.000°C and beyond
- Accuracy : +/- 1°C
- Probe sensor : thermocouple K
- Calibration : °C, °F, °K
- Memory : Maximum and Minimum readings
- F EN 61326-1 standard
- Shockproof container



Tension problem ?

EASYTEC, the universal Hutchinson tension meter



- Probe : laser
- Measuring : Hertz and Newtons
- Measuring range : from 10 to 340 Hz
- Accuracy : +/- 1 Hz



What's wrong with your belt drive ?

Hutchinson optical tachometer



- Measuring range : 60 to 50,000 rpm
- Reading : in 1 rpm increments
- Accuracy : +/- 1 rpm of reading
- Probe sensor : optical and by mechanical contact
- Unit includes a hold function and 2,4 m cable
- Memory : Maximum and Minimum readings
- F EN 61326-1 standard
- Shockproof container



Having a sore throat?

The Hutchinson set of pulley profile gauges



Our set of metal profile gauges for grooved pulleys (in J, K, L and M profiles) will help you to verify that :

- the pulleys are machined in compliance with the ISO specifications and standards
- the pulleys have the correct profil
- any pulley wear is within acceptable limits during maintenance checks.

HUTCHINSON



HUTCHINSON TRANSMISSION
POLY V @ SERVICE

Rue des Martyrs - B.P. 423 - 37304 Joué-les-Tours Cedex - Tel : + 33 2 47 48 39 99 - Fax : + 33 2 47 48 38 34

E-mail : polyv.service@hutchinson.fr

hutchinsontransmission.com